


SPESIFIKASI LAMPU PJU-TS 80 WATT LED OSRAM


1. LAMPU LED OSRAM 80 WATT HIGH LUMENS	2. Spesification LED OSRAM 80 Watt
	<ul style="list-style-type: none"> . Dual power source : Ac / Dc . Protection : IP 66 Design Outdoor . High efficacy : Up to 120lm/W . Lumens : 9600lm . Long lifetime : 50,000 hours . Warranty : 2 ~ 3 years . Material : Aluminum . Kelvin color / CCT : 4000K ~ 5600K . Beam Angle : 150 x 60


	<p style="text-align: center;">LEDENVO™ LED Street Light Photometrics Light Distribution Curve</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>150° x 60°</p>  <p>150° 180° 90° 30° 0° 30° 60° 90° 120° 150° 180° 210° 240° 270° 300° 330° 360° candle 0</p> <p>150° Beam Angle</p> </div> <div style="text-align: center;"> <p>150° x 70°</p>  <p>150° 180° 90° 30° 0° 30° 60° 90° 120° 150° 180° 210° 240° 270° 300° 330° 360° candle 0</p> <p>150° Beam Angle</p> </div> </div> <p style="font-size: small; text-align: center;"> Due to the repeating nature of LEDs, the actual luminous distribution and distance lumens may differ slightly from the actual parameters of the LED manufacturer. Specifications are subject to change without notice. Please refer to the actual product for the most current information. ©2015 LEDENVO™ All rights reserved. http://www.pjusolarcelltata.com </p>
---	---


PT.TATACIPTA PELANGI

<https://pjusolarcelltata.com/wp>

HUBUNGI : Mr. Asep & Ms. Budiwati : 081319121920 – 081319832763

1. Solar panel / PV Module	2. Spesification 120 Watt Pick / WP x 2 pcs
	<ul style="list-style-type: none"> . Module type : Poly Crystalline . Power Output : 240 watt . Voltage at Pmax, Impp : 17.5 Volt . Current at Pmax ,Impp : 13,7 Amper . Open circuit current Voc : 21.6 Volt . Short circuit current Isc : 14.2 Amper . Warranty : 15 years

1. Controller Smart SRNE 12/24 Volt {15-20 A}	2. Spesification SMART SRNE
	<ul style="list-style-type: none"> . Model type : Smart SRNE . Power Input : 12/24 volt . Voltage input PV : 15 ~ 55 Volt . Current Max : 5 ~ 20 Amper . Volttage Load LED : 15 ~ 60 Volt . Protection : IP 68 . Warranty : 1 years

1. Battery Vrla / lead acid	2. Spesification
	<ul style="list-style-type: none"> . Model type : Vrla – Lead acid . Power Amper : 100 Ah x 2 pcs { 200ah } 12volt . Voltage : 12.6 ~ 13.2 Volt . Lifetime : 2 years . Warranty : 1 years


[HUBUNGI : Mr. Asep & Ms. Budiwati : 081319121920 – 081319832763](tel:081319121920)

1. Box Battery	2. Spesification
-----------------------	-------------------------



- . Model type : Powder coating
Box susun 100Ah
- . Capacity Box Battery : 100 Ah x 2 pcs
{ 200Ah } 12volt
- . Lifetime : 2 years
- . Warranty : 1 years

1. Light poles & accessories	2. Spesification
---	-------------------------



- . Model type : Octagonal Galvanis
- . Capacity Box Battery : 200 Ah
- . Standart pole height : 8 ~ 9 M
- . Lifetime : 20 years
- . Warranty : 10 years